

# 400 Series 404D-22G ElectropaK

20.3 kWm @ 1500 rpm  
 23.9 kWm @ 1800 rpm  
 32.7 kWm @ 3000 rpm

The Perkins® 400 Series engine family continues to set new standards in the compact engine market. Developed alongside customers to fulfill their needs in the generator set, compressor, agricultural and general industrial markets.

These new ElectropaKs provide compact power, from a robust family of 3 and 4 cylinder diesel engines designed to provide economic and durable operation at prime and standby duties, hitting the key power nodes required by the power generation industry.

## Powered by your needs

- The 404D-22G ElectropaK is a powerful but quiet 2.2 litre naturally aspirated 4-cylinder compact package

## Compact, clean, efficient power

- Design features on the 400D range of ElectropaKs ensures clean rapid starting in all conditions whilst delivering impressive performance with low operating costs in a small, efficient package size

## Lower operating costs

- Approved for operation on biodiesel\* concentrations of up to 20%
- Oil and filter changes are 500 hours, dependent on load factor
- Engine durability and reliability, the warranty offering and ease of installation combine to drive down the cost of ownership

## Long-term power solution

- The 400D range of ElectropaKs has been designed to fully comply with stringent EU and EPA emissions regulations, providing an emissions compliant power solution for the future



## Product support

- With highly trained Perkins distributors in thousands of communities in over 180 countries, you are never far away from expert product knowledge, genuine parts and a range of advanced diagnostic technology for keeping your engine in peak condition

## Warranties and Service Contracts

We provide one-year warranties for constant speed engines and two-year warranties for variable speed models, as standard. These are supported by multilevel Extended Service Contracts that can be bought additionally

## Discover more

[www.perkins.com](http://www.perkins.com)  
[www.tier4air.com](http://www.tier4air.com)

[www.perkins.com/distributor](http://www.perkins.com/distributor)

To find your local distributor

Engine speed	Type of Operation	Typical Generator Output (Net)		Engine Power				Low Idle
				Gross		Net		
		kVA	kWe	kWm	hp	kWm	hp	
1500	Prime power	20.3	16.2	18.7	25.1	18.4	24.7	n/a
	Standby power	22.3	17.8	20.6	27.6	20.3	27.2	n/a
1800	Prime power	24.2	19.3	22.0	29.5	21.7	29.1	n/a
	Standby power	26.6	21.3	24.3	32.6	23.9	32.1	n/a
†3000	Prime power	33.1	26.5	31.2	41.8	29.7	39.9	1600 ± 25
	Standby power	36.4	29.1	34.4	46.1	32.7	43.9	1600 ± 25

\*Subject to conformance with ASTM D6751 and EN14214.

† Regarding gen sets ≥ 3000 rev/min: 'The U.S. EPA has certified this engine as a **constant speed** engine, with engine speed controlled by a solenoid that allows operation only at idle or full power position. The solenoid is a required element of design. **It is the responsibility of the equipment manufacturer to install the proper solenoid.** Installation of this engine in equipment without the required solenoid (or in any manner that allows variable speed operation) is not covered by EPA certification, voids the emissions warranty, and may subject the equipment manufacturer to penalties under U.S. law'.

The above ratings represent the engine performance capabilities to conditions specified in ISO 8528/1, ISO 3046/1:1986, BS 5514/1. Derating may be required for conditions outside these; consult Perkins Engines Company Limited. Generator powers are typical and are based on typical alternator efficiencies and a power factor (cos  $\phi$ ) of 0.8.

Fuel specification: BS 2869: Part 2 1998 Class A2 or ASTM D975 D2.

Rating Definitions: Prime Power: Power available at variable load in lieu of a main power network. Overload of 10% is permitted for 1 hour in every 12 hours operation. Standby (maximum): Power available at variable load in the event of a main power network failure. No overload is permitted.


Photographs are for illustrative purposes only and may not reflect final specification.

All information in this document is substantially correct at time of printing and may be altered subsequently.

Publication No.PN1911/06/12 Produced in England ©2012 Perkins Engines Company Limited

# 400 Series 404D-22G Electropak

20.3 kWm @ 1500 rpm  
 23.9 kWm @ 1800 rpm  
 32.7 kWm @ 3000 rpm



## Standard electropak specification

### Air inlet

- Mounted air filter

### Fuel system

- Mechanically governed cassette type fuel injection pump
- Split element fuel filter

### Lubrication system

- Wet steel sump with filler and dipstick
- Spin-on full-flow lub oil filter

### Cooling system

- Thermostatically-controlled system with belt driven coolant pump and pusher fan
- Mounted radiator, piping and guards

### Electrical equipment

- 12 volt starter motor and 12 volt 65 amp alternator with DC output
- Oil pressure and coolant temperature switches
- 12 volt shut-off solenoid energised to run
- Glow plug cold start aid and heater/starter switch

### Flywheel and housing

- 1500/1800 rev/min
- High inertia flywheel to SAE J620 Size 7½ Heavy
- Flywheel housing SAE 4 Long
- 3000 rev/min
- High inertia flywheel to SAE J620 Size 7½ Light
- Flywheel housing SAE 4 Short

### Mountings

- Front and rear engine mounting bracket

### Optional equipment

- Parts book

Fuel Consumption				
Engine Speed	1500 rpm		1800 rpm	
	g/kWh	l/hr	g/kWh	l/hr
Standby	244	6.1	235	6.9
Prime power	237	5.3	233	6.2
75% of prime power	238	4.0	240	4.8
50% of prime power	258	2.9	262	3.5

## General Data

Number of cylinders ..... 4  
 Cylinder arrangement ..... Vertical in-line  
 Cycle ..... 4 stroke  
 Aspiration ..... Naturally aspirated  
 Combustion system ..... Indirect injection  
 Compression ratio ..... 23.3:1  
 Bore and Stroke ..... 84 x 100 mm (3.3 x 3.9 in)  
 Displacement ..... 2.216 litres (135.2 cubic in)  
 Direction of rotation ..... Anti-clockwise viewed on flywheel  
 Cooling system ..... Water cooled  
 Total coolant capacity ..... 7.0 litres (1.8 US gals)  
 Total lubrication system capacity ..... 10.6 litres (2.8 US gals)  
 Dimensions  
     Length ..... 946 mm (37.2 in)  
     Width ..... 497 mm (19.6 in)  
     Height ..... 840 mm (33.0 in)  
 Total weight (dry) ..... 242 kg (533 lb)

Final weight and dimensions will depend on completed specification.

## Option groups

A selection of optional items is available to enable you to prepare a specification precisely matched to your needs.

## Emissions statement

**Constant Speed Engines** for use in Industrial, IOPU and Electropak applications: Certified against the requirements of EU Stage IIIA (Directives 97/68/EC, as last amended, for mobile applications); and US EPA Tier 4 Interim (40 CFR Parts 60 for stationary applications and 40 CFR Part 1039 for mobile applications).

Photographs are for illustrative purposes only and may not reflect final specification.

All information in this document is substantially correct at time of printing and may be altered subsequently.  
 Publication No. PN1901/06/12 Produced in England ©2012  
 Perkins Engines Company Limited

## Perkins Engines Company Limited

Peterborough PE1 5FQ  
 United Kingdom  
 Telephone +44 (0)1733 583000  
 Fax +44 (0)1733 582240  
[www.perkins.com](http://www.perkins.com)



THE HEART OF EVERY GREAT MACHINE